

CONTROLLI
ELETTRICI ed
ACCESSORI
CONTROL DEVICES and
ACCESSORIES

PRESSOSTATO BIG

BIG PRESSURE SWITCH

IP 55



Pressione Ammissibile / Permissible Pressure	28 MPa	4060 psi
Temperatura Nominale / Rated Temperature	90 °C	194 °F
Tensione / Voltage	250 V	
Int. corrente / Current Int.	15 A	

Codice Part No.	Tipo Type	Attacco Connection	Pressione Intervento Opening Pressure	Massa Weight		
				gr	oz	
21.0048	2 fili/wires	G 1/4 M	◆ 0.8 MPa-115 psi	255	8.99	20
21.0016	3 fili/wires	G 1/4 M	◆ 0.8 MPa-115 psi	255	8.99	20
21.0045	2 fili/wires	G 1/4 M	◆ 1.5 MPa-210 psi	255	8.99	20
21.0014	3 fili/wires	G 1/4 M	◆ 1.5 MPa-210 psi	255	8.99	20
21.0035	2 fili/wires	G 1/4 M	◆ 2.5 MPa-360 psi	255	8.99	20
21.0010	3 fili/wires	G 1/4 M	◆ 2.5 MPa-360 psi	255	8.99	20
21.0036	2 fili/wires	G 1/4 M	◆ 4 MPa-580 psi	255	8.99	20
21.0011	3 fili/wires	G 1/4 M	◆ 4 MPa-580 psi	255	8.99	20
21.0049	2 fili/wires	G 3/8 M	◆ 0.8 MPa-115 psi	270	9.52	20
21.0017	3 fili/wires	G 3/8 M	◆ 0.8 MPa-115 psi	270	9.52	20
21.0046	2 fili/wires	G 3/8 M	◆ 1.5 MPa-210 psi	270	9.52	20
21.0015	3 fili/wires	G 3/8 M	◆ 1.5 MPa-210 psi	270	9.52	20
21.0043	2 fili/wires	G 3/8 M	◆ 2.5 MPa-360 psi	270	9.52	20
21.0012	3 fili/wires	G 3/8 M	◆ 2.5 MPa-360 psi	270	9.52	20
21.0044	2 fili/wires	G 3/8 M	◆ 4 MPa-580 psi	270	9.52	20
21.0013	3 fili/wires	G 3/8 M	◆ 4 MPa-580 psi	270	9.52	20

PRESSOSTATO MICRO

MICRO PRESSURE SWITCH

IP 55



Pressione Ammissibile / Permissible Pressure	28 MPa	4060 psi
Temperatura Nominale / Rated Temperature	90 °C	195 °F
Tensione / Voltage	250 V	
Int. corrente / Current Int.	5 A	

Codice Part No.	Tipo Type	Attacco Connection	Pressione Intervento Opening Pressure	Massa Weight		
				gr	oz	
21.0008	3 fili/wires	G 1/8 M	◆ 1.5 MPa-210 psi	160	5.64	20
21.0007	3 fili/wires	G 1/8 M	◆ 2.5 MPa-360 psi	160	5.64	20
21.0009	3 fili/wires	G 1/8 M	◆ 4 MPa-580 psi	160	5.64	20
21.0002	3 fili/wires	G 1/4 M	◆ 1.5 MPa-210 psi	165	5.82	20
21.0001	3 fili/wires	G 1/4 M	◆ 2.5 MPa-360 psi	165	5.82	20
21.0003	3 fili/wires	G 1/4 M	◆ 4 MPa-580 psi	165	5.82	20
21.0005	3 fili/wires	G 3/8 M	◆ 1.5 MPa-210 psi	170	6.00	20
21.0004	3 fili/wires	G 3/8 M	◆ 2.5 MPa-360 psi	170	6.00	20
21.0006	3 fili/wires	G 3/8 M	◆ 4 MPa-580 psi	170	6.00	20

Voltaggio Ammissibile / Permissible Voltage	250 V
Intensità Ammissibile / Permissible Amperage	15 A
Lungh. serpentina / Coil length	1450 mm / 59"
Sonda / Probe	Ø6,5x95 mm - 0.26"x3.47"

TERMOSTATO con SONDA IMMERSA

THERMOSTAT with IMMERSED PROBE

Codice Part No.	Attacco Connection	Tipo Type	Temp. Nom. Rated Temp.	Massa Weight		
				gr	oz	
21.0054	M14x1 M	A	150 °C - 302 °F	125	4.41	5
21.0056	M14x1 M	A	90 °C - 194 °F	125	4.41	5
22.0090	1/2 BSPT M-14x1F	B	--	35	1.23	5



Voltaggio Ammissibile / Permissible Voltage	250 V
Intensità Ammissibile / Permissible Amperage	15 A
Lungh. serpentina / Coil length	1450 mm / 59"
Sonda / Probe	Ø6,5x95 mm - 0.26"x3.47"

TERMOSTATO con SONDA ESTERNA

THERMOSTAT with REMOTE PROBE

Codice Part No.	Temp. Nom. Rated Temp.	Massa Weight		
		gr	oz	
21.0053	150 °C - 302 °F	147	5.19	5



Materiale / Material	Ottone	Brass
Diametro di Passaggio / Passage Diameter	Ø7 mm	0.28"

GUAINA TERMOSTATO

THERMOSTAT SHEAT

Codice Part No.	Attacco Connection	Lunghezza Length	Massa Weight		
			gr	oz	
39.0050	1/2 BSPT M	50 mm - 2"	65	2.29	5
22.0089	1/2 BSPT M	101 mm - 4"	80	2.82	5



Pressione Ammissibile / Permissible Pressure	32 MPa	4640 psi
Temperatura Nominale / Rated Temperature	160 °C	320 °F
Materiale / Material	Ottone	Brass

POZZETTO PORTA SONDA

THERMOSTAT HOLDER SHAFT

Codice Part No.	Attacco Connection	Entrata Inlet	Uscita Outlet	Massa Weight		
				gr	oz	
22.0091	G 1/2 F	G 3/8 F	G 3/8 F-G 3/8 F	292	10.30	5



Note/Notes

A series of 30 horizontal gray lines, evenly spaced, extending across the width of the page. These lines are intended for writing notes.