



# SPAZZOLE BRUSHES

## EIETTORE ADDENSANTE SCHIUMA per SPAZZOLE

FOAM THICKENER FOR BRUSHES



| Codice<br>Part No. | Entrata<br>Inlet | Uscita<br>Outlet | Ugello<br>Nozzle  | Materiale<br>Material | Massa<br>Weight |      |    |
|--------------------|------------------|------------------|-------------------|-----------------------|-----------------|------|----|
|                    |                  |                  |                   |                       | gr              | oz   |    |
| 26.0021            | G 1/4 F          | G 1/4 M          | Ø 2.5 mm** - 0,1" | Inox / S.Steel        | 50              | 1.76 | 10 |

\*\* Per eventuali ugelli di riduzione vedere a pagina 71  
For reduction nozzles see page 71

## SPAZZOLA CAR WASH FB05 con SETOLE NATURALI

FB05 CAR WASH BRUSH with NATURAL BRISTLES



|  |          |                 |
|--|----------|-----------------|
| Pressione Ammissibile / Permissible Pressure | 0.5 MPa  | 72.5 psi        |
| Flusso Nominale / Rated Flow                 | 60 l/min | 16 U.S. gal/min |
| Temperatura Nominale / Rated Temperature     | 60 °C    | 140 °F          |

| Codice<br>Part No. | Entrata<br>Inlet | Materiale<br>Material                         | Lungh.<br>Setole<br>Brush Length | Massa<br>Weight |       |    |
|--------------------|------------------|---|----------------------------------|-----------------|-------|----|
|                    |                  |   |                                  | gr              | oz    |    |
| 26.0013            | G 1/4 F          | 100% Setole naturali<br>100% Natural bristles | 60 mm - 2.4"                     | 565             | 19.93 | 10 |
| 26.0014            | G 1/4 F          | 100% Setole naturali<br>100% Natural bristles | 90 mm - 3.5"                     | 585             | 20.64 | 10 |

## SPAZZOLA CAR WASH FB05 con SETOLE MISTE

FB05 CAR WASH BRUSH in MIXED BRISTLES



|  |          |                 |
|--|----------|-----------------|
| Pressione Ammissibile / Permissible Pressure | 0.5 MPa  | 72.5 psi        |
| Flusso Nominale / Rated Flow                 | 60 l/min | 16 U.S. gal/min |
| Temperatura Nominale / Rated Temperature     | 60 °C    | 140 °F          |

| Codice<br>Part No. | Entrata<br>Inlet | Materiale<br>Material  | Lungh.<br>Setole<br>Brush Length | Massa<br>Weight |       |    |
|--------------------|------------------|--|----------------------------------|-----------------|-------|----|
|                    |                  |  |                                  | gr              | oz    |    |
| 26.0186            | G 1/4 F          | Setole 50% naturali - 50% Sintetiche<br>50% Natural - 50% Synthetic Bristles | 60 mm - 2.4"                     | 445             | 15.70 | 10 |
| 26.0187            | G 1/4 F          | Setole 50% naturali - 50% Sintetiche<br>50% Natural - 50% Synthetic Bristles | 90 mm - 3.5"                     | 565             | 19.93 | 10 |
| 26.0189            | 1/2 NPT F        | Setole 50% naturali - 50% Sintetiche<br>50% Natural - 50% Synthetic Bristles | 60 mm - 2.4"                     | 515             | 18.17 | 10 |
| 26.0190            | 1/2 NPT F        | Setole 50% naturali - 50% Sintetiche<br>50% Natural - 50% Synthetic Bristles | 90 mm - 3.5"                     | 515             | 22.40 | 10 |

Non utilizzare in assenza di acqua, a temperature superiori a quelle consentite o per il lavaggio di motori, marmitte, cerchi  
Avoid dry use. Do not exceed the rated temperature. Do not wash engines, wheels, exhausts.

## SPAZZOLA CAR WASH in DUE PEZZI CAR WASH BRUSH in TWO PIECES

Temperatura Nominale / Rated Temperature 60 °C 140 °F

| Codice<br>Part No. | Tipo<br>Type   | Massa<br>Weight |       |   |
|--------------------|--|-----------------|-------|---|
|                    |  | gr              | oz    |   |
| 26.0018 <b>A</b>   | Ricambio con Setole Naturali 60 mm<br>Replacement 2.4" Natural Bristles  | 400             | 14.11 | 5 |
| 26.0019 <b>A</b>   | Ricambio con Setole Naturali 90 mm<br>Replacement 3.5" Natural Bristles  | 420             | 14.82 | 5 |
| 26.0017 <b>B</b>   | Supporto Plastica G 1/4 F<br>Plastic Support G 1/4 F   | 65              | 2.29  | 5 |
| 26.0128 <b>C</b>   | Supporto Antiscippo in Plastica G 1/4 F completo di viti<br>Plastic Anti-Theft Cover Support G 1/4 F with screws | 70              | 2.47  | 5 |
| 26.0020 <b>D</b>   | Coperchio Antiscippo in Plastica<br>Plastic Anti-Theft Cover   | 85              | 3.00  | 5 |



Pressione Ammissibile / Permissible Pressure 3 MPa 435 psi  
Flusso Nominale / Rated Flow 60 l/min 16 U.S. gal/min  
Temperatura Nominale / Rated Temperature 30 °C 86 °F

| Codice<br>Part No. | Tipo Spazzola<br>Brush Type                       | Ugello<br>Nozzle  | Entrata<br>Inlet | Massa<br>Weight |       |   |
|--------------------|---|-------------------|------------------|-----------------|-------|---|
|                    |   |                   |                  | gr              | oz    |   |
| 26.0009 <b>A</b>   | Setole in Nylon bianco<br>White Nylon Bristles    | ∅ 3 mm<br>∅ 0.12" | G 1/4 M          | 916             | 32.31 | 1 |
| 26.0010 <b>B</b>   | Setole in Crine di Cavallo<br>Horse Hair Bristles | ∅ 3 mm<br>∅ 0.12" | G 1/4 M          | 903             | 31.85 | 1 |



## RB3 SPAZZOLA ROTANTE RB3 ROTATING BRUSH

Pressione Ammissibile / Permissible Pressure 0.5 MPa 72.5 psi  
Temperatura Nominale / Rated Temperature 30 °C 86 °F

| Codice<br>Part No. | Tipo Spazzola<br>Brush Type                    | Entrata<br>Inlet | Massa<br>Weight |      |   |
|--------------------|--|------------------|-----------------|------|---|
|                    |  |                  | gr              | oz   |   |
| 26.0047            | Setole in Nylon bianco<br>White Nylon Bristles | G 1/4 F          | 210             | 7.41 | 5 |



## TB05 SPAZZOLA FISSA TB05 FIXED BRUSH

# Note/Notes

A series of 25 horizontal gray lines, evenly spaced, extending across the width of the page. These lines are intended for writing notes.