

EIETTORI  
DETERGENTI  
CHEMICAL INJECTORS

## EIETTORE DETERGENTE FISSO G 3/8 M - G 3/8 M

FIXED CHEMICAL INJECTOR G 3/8 M - G 3/8 M



Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0019	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	110	3.88	10
22.0020	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	110	3.88	10
22.0021	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	110	3.88	10
22.0022	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	110	3.88	10

Ugello inox + OR viton® / S.Steel nozzle + viton® o-ring

## EIETTORE DETERGENTE FISSO ACID G 3/8 M - G 3/8 M

ACID FIXED CHEMICAL INJECTOR G 3/8 M - G 3/8 M



Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0353	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	110	3.88	10
22.0354	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	110	3.88	10
22.0355	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	110	3.88	10
22.0356	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	110	3.88	10

Specifico per aspirazione detergenti acidi aggressivi / Specific for suction acid chemicals

## EIETTORE DETERGENTE REGOLABILE G 3/8 M - G 3/8 M

ADJUSTABLE CHEMICAL INJECTOR G 3/8 M - G 3/8 M



Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0040	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	147	5.19	10
22.0041	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	147	5.19	10
22.0039	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	147	5.19	10
22.0042	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	147	5.19	10

Ugello inox + OR viton® / S.Steel nozzle + viton® o-ring

## EIETTORE DETERGENTE REGOLABILE ACID G 3/8 M - G 3/8 M

ACID ADJUSTABLE CHEMICAL INJECTOR G 3/8 M - G 3/8 M



Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F


Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0357	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	147	5.19	10
22.0358	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	147	5.19	10
22.0359	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	147	5.19	10
22.0360	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	147	5.19	10

Specifico per aspirazione detergenti acidi aggressivi / Specific for suction acid chemicals

## EIETTORE DETERGENTE FISSO G 3/8 M - G 3/8 F

### FIXED CHEMICAL INJECTOR G 3/8 M - G 3/8 F

Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0027	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	158	5.54	10
22.0028	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	158	5.54	10
22.0029	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	158	5.54	10
22.0030	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	158	5.54	10


Ugello inox + OR viton® / S.Steel nozzle + viton® o-ring



## EIETTORE DETERGENTE REGOLABILE G 3/8 M - G 3/8 F

### ADJUSTABLE CHEMICAL INJECTOR G 3/8 M - G 3/8 F

Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0047	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	195	6.88	10
22.0048	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	195	6.88	10
22.0049	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	195	6.88	10
22.0050	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	195	6.88	10


Specifico per aspirazione detergenti acidi aggressivi / Specific for suction acid chemicals



## EIETTORE DETERGENTE FISSO G 3/8 F - G 3/8 M

### FIXED CHEMICAL INJECTOR G 3/8 F - G 3/8 M

Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0031	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	128	4.52	10
22.0032	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	128	4.52	10
22.0033	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	128	4.52	10
22.0034	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	128	4.52	10


Ugello inox + OR viton® / S.Steel nozzle + viton® o-ring



## EIETTORE DETERGENTE REGOLABILE G 3/8 F - G 3/8 M

### ADJUSTABLE CHEMICAL INJECTOR G 3/8 F - G 3/8 M

Pressione Ammissibile / Rated Pressure 28 MPa 4060 psi  
 Temperatura Nominale / Rated Temperature 150 °C 302 °F

Codice Part No.	Ugello Nozzle	Flusso Flow	Massa Weight		
			gr	oz	
22.0051	Ø 1.6 mm - 0.063"	8-12 l/min - 8.1-3.2 U.S. gal/min	165	5.82	10
22.0052	Ø 1.8 mm - 0.071"	12-16 l/min - 3.2-4.2 U.S. gal/min	165	5.82	10
22.0053	Ø 2.1 mm - 0.083"	16-21 l/min - 4.2-5.5 U.S. gal/min	165	5.82	10
22.0054	Ø 2.3 mm - 0.091"	21-25 l/min - 5.5-6.6 U.S. gal/min	165	5.82	10

Specifico per aspirazione detergenti acidi aggressivi / Specific for suction acid chemicals



