

## Small submersible centrifugal pump

### Applications

Pumping and recirculation of clean water.  
Suitable for fountains, aquariums, ponds, air conditioners condensate removal...

### Motor

Asynchronous 2 poles.  
IP 68 protection.  
Class F insulation.  
Water cooled motor.  
Continuous operation.

### Materials

Pump in technopolymer.

### Limitations

Maximum water temperature: 40°C.

### Equipment

Decor 03/04/08/12: 1,5m of cable with plug type F.  
Decor 25/40/60: 3m of cable with plug type F and unions included.



Decor 03/04/08/12



Decor 25/40/60

### Hydraulic performance table

Model	I [A]	P1 [kW]	l/min	1,7	3,3	5	6,6	8,3	10	11,6	13,3	16,6	Code
	1~230V	1~230V	m³/h	0,1	0,2	0,3	0,4	0,5	0,6	0,7	0,8	1	
Decor 03	0,02	3,8	mwc	0,4	0,2	0,1	-	-	-	-	-	-	102935
Decor 04	0,04	6		0,5	0,4	0,2	-	-	-	-	-	-	102936
Decor 08	0,07	10		1,4	1,1	1	0,8	0,6	0,5	0,2	-	-	102937
Decor 12	0,23	25		2	1,8	1,7	1,6	1,5	1,4	1,2	1	0,5	102938

Model	I [A]	P1 [kW]	l/min	10	16,6	23,3	30	36,6	43,3	56,6	70	83,3	Code
	1~230V	1~230V	m³/h	0,6	1	1,4	1,8	2,2	2,6	3,4	4,2	5	
Decor 25	0,51	55	mwc	2,6	2,3	1,8	1,4	0,7	-	-	-	-	102939
Decor 40	0,64	67		2,8	2,7	2,5	2,3	2	1,7	0,6	-	-	102940
Decor 60	0,81	90		3,7	3,6	3,5	3,4	3,3	3	2,5	1,9	0,7	102941

### Dimension and weight

Model	A	B	C	Ø discharge
Decor 03	42	36	59	13
Decor 04	43	52	57	13
Decor 08	45	61	60	13
Decor 12	55	72	83	20
Decor 25	96	104	131	1"
Decor 40	96	104	131	1"
Decor 60	111	133	160	1"

