

Filterkit Plus Swimming Pool



Filters with valves

Filterkit Plus

Filters with valves made of chemical and weather-resistant modified polypropylene.

Injection moulded, with the two halves thermally welded.

Highly versatile six-way valve.

Highest quality, from Ø520 to Ø760 mm for pools with a volume of water up to 176 m³.

Features

Working pressure: 2.5 bar; maximum pressure: 3.5 bar.

Connection with 1 1/2" six-way valve for Ø520 and Ø620 mm models; 2" for Ø760 mm models.

Fitted with pressure gauge and air valve.

Double drainage in the lower section of the filter: 1 1/2" to totally empty the filter; 1/2" to drain water without loss of sand.

Transparent lid for easy inspection.

Valve lid to the filter via a 203 mm anti-blockage seal.



Check conditions and terms at page 29

Characteristics

Model	Filter				Code
	Ø filter [mm]	Nominal flow [m ³ /h]	* Max. pool volume [m ³]	Silex load [Kg]	
FKP 520 6LT	520	10	88	85	130906
FKP 620 6LT	620	15	128	145	130907
FKP 760 6LT	760	22	184	300	130908

(*) Maximum swimming pool volume (m³): considering water circulation of 8 hours/day at 10 mwc.

Dimensions and weights

Model	A	B	C	D	E	Ø	Kg
FKP 520 6LT	844	886	422	460	519	520	21,7
FKP 620 6LT	943	957	422	501	560	620	23,7
FKP 760 6LT	1.102	1.114	422	630	715	767	34,0

