

# Filterpak Plus Swimming Pool



## Filters with valves

### Filterpak Plus

Compact filter and pump units in pools up to 176 m<sup>3</sup>.

Highly versatile, with top or side-mounted, six-way valve.

Maximum quality, with injection-moulded filters from Ø520 up to Ø760 mm and pumps up to 1.5 HP.

### Features

Compact centrifugal pump.

Thermally welded, modified polypropylene filter.

Six-way valve 1 1/2" in the Ø520 mm and Ø620 mm models; 2" in the Ø760 mm model.

Base unit in modified polypropylene.

Rigid pump-filter connection kit.



Check conditions and terms at page 29

## Characteristics

Model	Filter				Pump			Valve	Code	Components		
	Ø filter [mm]	Nominal flow [m <sup>3</sup> /h]	* Max. pool volume [m <sup>3</sup> ]	Silex load [Kg]	P2 (HP)	I (A) 1~	Ø Suc. (mm)	Connection		Pump Code	Filter Code	Base Code
FPP 520 6LT SILEN S 75 15M	520	15,0	88	85	0,75	5,5	63/50	1 1/2"	132669	203148	130906	203121
FPP 620 6LT SILEN S 100 18M	620	18,0	128	145	1,0	6	63/50	1 1/2"	132671	203149	130907	203121
FPP 760 6LT SILEN S 150 22M	760	22,0	184	300	1,5	7,1	63/50	2"	132673	203150	130908	203122

(\*) Maximum swimming pool volume (m<sup>3</sup>): considering water circulation of 8 hours/day at 10 mwc.

## Dimensions and weights

Model	A	B	C	D	E	F	Kg
FPP 520 6LT SILEN S 75 15M	803	866	744	845	463	524	34,1
FPP 620 6LT SILEN S 100 18M	853	957	744	945	501	562	38,6
FPP 760 6LT SILEN S 150 22M	1054	1100	871	1076	630	711	51,6

