

Filterkit Base Swimming Pool



Filters with valves

Filterkit Base

Filters with valves made of chemical and weather-resistant polyethylene. Moulded in single piece, with base built into the filter. Highly versatile, with top mounted, four or six-way valve.

Features

Working pressure: 2 bar; maximum pressure: 2.5 bar. Top connection with 1 1/2" four or six way valve. Fitted with pressure gauge and air valve. Double drainage in the lower section of the filter: 1/2" to totally empty the filter; 1/4" to drain water without loss of sand. Transparent lid on the side-mounted version for easy inspection. Filter connected to valve via a 177 mm clamp.



Check conditions and terms at page 29

Characteristics

Model	Filter				Code
	Ø filter [mm]	Nominal flow [m³/h]	* Max. pool volume [m³]	Silex load [Kg]	
FKB 350 4TP	350	6	48	35	134537
FKB 450 6TP	450	8	64	75	134538
FKB 550 6TP	550	12	96	125	134539

(*) Maximum swimming pool volume (m³): considering water circulation of 8 hours/day at 10 mwc.

Dimensions and weights

Model	A	B	C	Ø	Kg
FKB 350 4TP	-	735	258	350	5,6
FKB 450 6TP	-	832	330	450	7,7
FKB 550 6TP	-	832	440	550	10,1

