




water solutions

Data sheet



DGG 300/2/65 C0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10kW: paragraph 4.4.2
10kW < P2 < 100kW: Grade 3B
P2 > 100kW: Grade 2B



[mm (inch)]

Pump

Series	GREY series
Pump name	DGG 300/2/65 C0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	2,2 kW
Incoming power P1	2,76 kW
Rated current	4,62 A
rpm	2880 1/min
Efficiency	79,7 %
cos φ	0,862
Rated torque	7,3 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	65 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	27,6 %
Suction	DN 65 UNDRILLED
Discharge	DN 65 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	46,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 300/2/65 C0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 65 mm	Discharge DN 65	Suction DN 65
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 300/2/65 C0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 65 EN 1092-2	Suction: DN 65 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 65/65V+KAF 116-2" EN (P)		Accessory code 9001.031
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

zenit.com

Created on 2019-03-04

Page 3 / 3




water solutions

Data sheet



DGG 300/2/80 G0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B

[mm
[inch]

Pump

Series	GREY series
Pump name	DGG 300/2/80 G0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	2,2 kW
Incoming power P1	2,76 kW
Rated current	4,62 A
rpm	2880 1/min
Efficiency	79,7 %
cos φ	0,862
Rated torque	7,3 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	80 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	22,5 %
Suction	DN 80 UNDRILLED
Discharge	DN 80 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	44,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded

Rev. 0 - 16-12-2014

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

Created on 2019-03-04

zenit.com

Page 1 / 3



water solutions

Data sheet


DGG 300/2/80 G0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 80 mm	Discharge DN 80	Suction DN 80
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s




Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 80 EN 1092-2	Suction: DN 80 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 80/80V+KAF 116-2" EN (P)		Accessory code 9001.032
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)




water solutions

Data sheet



DGG 300/2/G65V A0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10kW: paragraph 4.4.2
10kW < P2 < 100kW: Grade 3B
P2 > 100kW: Grade 2B



[mm (inch)]

Pump

Series	GREY series
Pump name	DGG 300/2/G65V A0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	2,2 kW
Incoming power P1	2,76 kW
Rated current	4,62 A
rpm	2880 1/min
Efficiency	79,7 %
cos φ	0,862
Rated torque	7,3 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	65 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	25,2 %
Suction	DN 65 UNDRILLED
Discharge	G 2" 1/2 -
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	44,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded




water solutions

Data sheet

DGG 300/2/G65V A0ET5**GREY**
series**Pump performance curves****3~ 50 Hz**

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 65 mm	Discharge G 2" 1/2	Suction DN 65
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012

P2<10kW: paragraph 4.4.2

10kW<P2<100kW: Grade 3B

P2>100kW: Grade 2B




water solutions

Data sheet

DGG 300/2/G65V A0ET5**GREY**
series**Dimensional drawing****3~ 50 Hz**

Installation type Installation with base plate		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge G 2" 1/2 -	Suction: DN 65 UNDRILLED	Pressure rating (suction/discharge) -
Accessory KBS 3F I184 (S)		Accessory code 9024.006
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)



water solutions


Data sheet

DGG 300/4/65 F0ET5


GREY
series

Technical specification

3~ 50 Hz



Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10kW: paragraph 4.4.2
10kW < P2 < 100kW: Grade 3B
P2 > 100kW: Grade 2B



Pump

Series	GREY series
Pump name	DGG 300/4/65 F0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	2,2 kW
Incoming power P1	2,7 kW
Rated current	5,15 A
rpm	1410 1/min
Efficiency	81,5 %
cos φ	0,77
Rated torque	14,9 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	65 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	47,4 %
Suction	DN 65 UNDRILLED
Discharge	DN 65 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	58,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 300/4/65 F0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 65 mm	Discharge DN 65	Suction DN 65
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B




water solutions

Data sheet

DGG 300/4/65 F0ET5**GREY**
series**Dimensional drawing****3~ 50 Hz**

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 65 EN 1092-2	Suction: DN 65 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 65/65V+KAF 116-2" EN (P)		Accessory code 9001.031
Note: Accessory must be ordered separately		

[mm
[inch]

L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

zenit.com

Created on 2019-03-04

Page 3 / 3




water solutions

Data sheet



DGG 300/4/80 E0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10kW: paragraph 4.4.2
10kW < P2 < 100kW: Grade 3B
P2 > 100kW: Grade 2B

[mm
(inch)]

Pump

Series	GREY series
Pump name	DGG 300/4/80 E0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	2,2 kW
Incoming power P1	2,7 kW
Rated current	5,15 A
rpm	1410 1/min
Efficiency	81,5 %
cos φ	0,77
Rated torque	14,9 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	80 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	46,3 %
Suction	DN 80 UNDRILLED
Discharge	DN 80 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	58,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 300/4/80 E0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 80 mm	Discharge DN 80	Suction DN 80
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B




water solutions

Data sheet

DGG 300/4/80 E0ET5**GREY**
series**Dimensional drawing****3~ 50 Hz**

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 80 EN 1092-2	Suction: DN 80 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 80/80V+KAF 116-2" EN (P)		Accessory code 9001.032
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

zenit.com

Created on 2019-03-04

Page 3 / 3




water solutions

Data sheet



DGG 300/4/100 E0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10 kW: paragraph 4.4.2
10 kW < P2 < 100 kW: Grade 3B
P2 > 100 kW: Grade 2B



[mm (inch)]

Pump

Series	GREY series
Pump name	DGG 300/4/100 E0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	2,2 kW
Incoming power P1	2,7 kW
Rated current	5,15 A
rpm	1410 1/min
Efficiency	81,5 %
cos φ	0,77
Rated torque	14,9 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	100 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	39,6 %
Suction	DN 100 UNDRILLED
Discharge	DN 100 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	61,2 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded

Rev. 0 - 16-12-2014

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

Created on 2019-03-04

zenit.com

Page 1 / 3



water solutions

Data sheet


DGG 300/4/100 E0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 100 mm	Discharge DN 100	Suction DN 100
DUTY POINT					
Flow	Head	Shaft power P₂	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 300/4/100 E0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 100 EN 1092-2	Suction: DN 100 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 100/100V+KAF 116-2" EN (P)		Accessory code 9001.033
Note: Accessory must be ordered separately		




L1: Minimum operating level for continuous use



L2: Minimum operating level for discontinuous use (only "WET" version)

Technical specification

3~ 50 Hz



Characteristic curves according to UNI EN ISO 9906:2012

[mm]
[inch]

Pump

Series	GREY series
Pump name	DGG 400/2/65 D0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	3 kW
Incoming power P1	3,68 kW
Rated current	6,36 A
rpm	2877 1/min
Efficiency	81,5 %
cos φ	0,835
Rated torque	10,0 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	65 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	28,1 %
Suction	DN 65 UNDRILLED
Discharge	DN 65 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	50 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 400/2/65 D0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 65 mm	Discharge DN 65	Suction DN 65
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 400/2/65 D0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 65 EN 1092-2	Suction: DN 65 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 65/65V+KAF 116-2" EN (P)		Accessory code 9001.031
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)




water solutions

Data sheet



DGG 400/2/80 H0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10 kW: paragraph 4.4.2
10 kW < P2 < 100 kW: Grade 3B
P2 > 100 kW: Grade 2B



[mm (inch)]

Pump

Series	GREY series
Pump name	DGG 400/2/80 H0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	2
Rated power P2	3 kW
Incoming power P1	3,68 kW
Rated current	6,36 A
rpm	2877 1/min
Efficiency	81,5 %
cos φ	0,835
Rated torque	10,0 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	80 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	19,5 %
Suction	DN 80 UNDRILLED
Discharge	DN 80 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	47 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 400/2/80 H0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 80 mm	Discharge DN 80	Suction DN 80
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 400/2/80 H0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 80 EN 1092-2	Suction: DN 80 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 80/80V+KAF 116-2" EN (P)		Accessory code 9001.032
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)

All data shown are not binding. Zenit reserves the right to change data and dimensions without notice.

zenit.com

Created on 2019-03-04

Page 3 / 3




water solutions

Data sheet


DGG 400/4/65 G0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10 kW: paragraph 4.4.2
10 kW < P2 < 100 kW: Grade 3B
P2 > 100 kW: Grade 2B



Pump

Series	GREY series
Pump name	DGG 400/4/65 G0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	3 kW
Incoming power P1	3,68 kW
Rated current	6,72 A
rpm	1383 1/min
Efficiency	81,5 %
cos φ	0,79
Rated torque	20,7 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	65 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	50,9 %
Suction	DN 65 UNDRILLED
Discharge	DN 65 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	59,8 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 400/4/65 G0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 65 mm	Discharge DN 65	Suction DN 65
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 400/4/65 G0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 65 EN 1092-2	Suction: DN 65 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 65/65V+KAF 116-2" EN (P)		Accessory code 9001.031
Note: Accessory must be ordered separately		


 DN 65 PN10-16
 EN 1092-2

L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)




water solutions

Data sheet



DGG 400/4/80 M0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10kW: paragraph 4.4.2
10kW < P2 < 100kW: Grade 3B
P2 > 100kW: Grade 2B

[mm
(inch)]

Pump

Series	GREY series
Pump name	DGG 400/4/80 M0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	3 kW
Incoming power P1	3,68 kW
Rated current	6,72 A
rpm	1383 1/min
Efficiency	81,5 %
cos φ	0,79
Rated torque	20,7 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	80 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	48,8 %
Suction	DN 80 UNDRILLED
Discharge	DN 80 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	59,8 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 400/4/80 M0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 80 mm	Discharge DN 80	Suction DN 80
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B




water solutions

Data sheet

DGG 400/4/80 M0ET5**GREY**
series**Dimensional drawing****3~ 50 Hz**

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 80 EN 1092-2	Suction: DN 80 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 80/80V+KAF 116-2" EN (P)		Accessory code 9001.032
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)




water solutions

Data sheet



DGG 400/4/100 D0ET5

GREY
series

Technical specification

3~ 50 Hz


Characteristic curves according to UNI EN ISO 9906:2012
P2 < 10 kW: paragraph 4.4.2
10 kW < P2 < 100 kW: Grade 3B
P2 > 100 kW: Grade 2B

[mm
(inch)]

Pump

Series	GREY series
Pump name	DGG 400/4/100 D0ET5
Configuration	NGTSB51040N00NN
Standard	CE

Motor data

Rated voltage	400 V
Frequency	50 Hz
Motor phases	3~
Number of poles	4
Rated power P2	3 kW
Incoming power P1	3,68 kW
Rated current	6,72 A
rpm	1383 1/min
Efficiency	81,5 %
cos φ	0,79
Rated torque	20,7 Nm
Start	Direct starting
Degree of protection	IP 68
Insulation class	H

Hydraulic

Type	DG (Set-back Vortex)
Free passage	100 mm
Impeller type	Set-back Vortex impeller
Max. hydraulic efficiency	38,7 %
Suction	DN 100 UNDRILLED
Discharge	DN 100 EN 1092-2
Curve tolerance	UNI EN ISO 9906:2012

Operating limits (standard pumps)

Max. ambient temperature	40 °C
Max. density treated liquid	1100 kg/m³
pH treated liquid	6 ÷ 14
Max. start per hour (equally distributed)	30
Wet/dry use	WET
Max. acoustic pressure level	70 dB
Operating mode	S1 - Continuous use

Construction materials

Case	Cast iron EN-GJL 250
Shaft	Stainless steel AISI 431
Hydraulic	Cast iron EN-GJL 250
Impeller	Cast iron EN-GJL 250
Painting/Coating	Bi-epoxy 200 µm sea water resistant
Screws	Stainless steel - Class A2-70
Gaskets	NBR

Construction features

Cooling system	No cooling jacket
Main cable	4G1,5 + 3x1
Cable length	10 mt
Mechanical seals	2 in silicon carbide (2SiC)
Additional drilling	-
Weight*	62,8 kg
Electrical variant	Thermal protection and leakage sensor

* cable, stand and guiding system excluded



water solutions

Data sheet


DGG 400/4/100 D0ET5

GREY
series

Pump performance curves

3~ 50 Hz

Hydraulic type DG (Set-back Vortex)		Impeller type Set-back Vortex impeller	Free passage 100 mm	Discharge DN 100	Suction DN 100
DUTY POINT					
Flow	Head	Shaft power P2	Hydraulic efficiency	Density 998,3 kg/m ³	Viscosity 1,005 mm ² /s



Characteristic curves according to UNI EN ISO 9906:2012
P2<10kW: paragraph 4.4.2
10kW<P2<100kW: Grade 3B
P2>100kW: Grade 2B



water solutions

Data sheet


DGG 400/4/100 D0ET5

GREY
series

Dimensional drawing

3~ 50 Hz

Installation type Installation with bottom coupling device - Vertical outlet		
Wet/dry use WET	Drilling variant N	Flushing valve - drilling -
Discharge DN 100 EN 1092-2	Suction: DN 100 UNDRILLED	Pressure rating (suction/discharge) -/PN 10
Accessory DAC 100/100V+KAF 116-2" EN (P)		Accessory code 9001.033
Note: Accessory must be ordered separately		



L1: Minimum operating level for continuous use

L2: Minimum operating level for discontinuous use (only "WET" version)