

-  Clean water
-  Domestic use
-  Civil use



TOP MULTI 1



TOP MULTI 2-3-4-5

PERFORMANCE RANGE

- Flow rate up to **120 l/min** (7.2 m³/h)
- Head up to **52 m**

INSTALLATION AND USE

TOPMULTI® pumps are designed to transfer **clean water** free from abrasive particles and liquids that will not damage the pump's components. Efficient and reliable, they are ideal for domestic applications involving tanks, reservoirs, and deep wells. They are also perfect for collecting rainwater from water tanks (rain barrels) for manual watering or irrigation systems.

APPLICATION LIMITS

- Maximum operating depth below water level:
 - up to **3 m** for TOP MULTI 1
 - up to **10 m** for TOP MULTI 2-3-4-5 (with an appropriately sized power cable)
- Liquid temperature up to **+40 °C**
- Draining capability:
 - up to **25 mm** from the bottom for TOP MULTI 1
 - up to **35 mm** from the bottom for TOP MULTI 2-3-4-5

INCLUDES

- ✳ Power cable length **10 m**
- ✳ Float switch
- ✳ Anti-vibration feet
- ✳ Hose connector **Ø 35 mm**
- ✳ Sleeve with clapet valve (for TOP MULTI 2-3-4-5)



PATENTS - TRADE MARKS - MODELS

- Registered Community Model No. 000885587 for TOP MULTI 2-3-4-5
- TOP MULTI® Registered trademark No. 0001334477


AVAILABLE UPON REQUEST

- ✳ Different voltage or frequency


CURVES AND PERFORMANCE DATA

60 Hz

TOP MULTI 1 - 2 - 4



TOP MULTI 3 - 5



TOP MULTI 1 - 2 - 4

TYPE	POWER (P ₂)		Q	m ³ /h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8
	kW	HP		l/min	0	10	20	30	40	50	60	70	80
Single-phase													
TOP MULTI 1	0.37	0.50	H	m	26	25	23.5	21.6	19.3	16.8	14	11	8
TOP MULTI 2	0.55	0.75		39	37.5	35.5	32.5	29	25	21	16.6	12	
TOP MULTI 4	0.75	1		52	50	47	43	38.5	33.5	28	22.1	16	

TOP MULTI 3 - 5

TYPE	POWER (P ₂)		Q	m³/h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0	6.6	7.2
Single-phase	kW	HP		l/min	0	10	20	30	40	50	60	70	80	90	100	110	120
TOP MULTI 3	0.55	0.75	H	m	30.5	30	29	27.5	26	24.3	22.2	19.8	17.2	14.4	11.3	8	4.5
TOP MULTI 5	0.75	1		41	40	38.5	37	35	32.5	29.5	26.5	22.9	19.2	15.1	10.7	6	

Q = Flow rate H = Total manometric head

Performance curves comply with EN ISO 9906 Grade 3B tolerance limits.

ABSORPTION



TYPE	VOLTAGE
Single-phase	220 V
TOP MULTI 1	2.3 A
TOP MULTI 2	3.4 A
TOP MULTI 3	3.4 A
TOP MULTI 4	4.3 A
TOP MULTI 5	4.7 A

TYPE	VOLTAGE
Single-phase	110 V
TOP MULTI 1	4.8 A
TOP MULTI 2	6.9 A
TOP MULTI 3	6.9 A
TOP MULTI 4	8.6 A
TOP MULTI 5	9.4 A



TOP MULTI

DIMENSIONS AND WEIGHT

TOP MULTI 1



TOP MULTI 2-3-4-5



TYPE	PORT DN	NO. STAGES	DIMENSIONS mm								kg		
			a	b	h	h1	d	e	p	∅			
TOP MULTI 1	1¼"	2	170	192	295	315	25	adjustable	350	350	6.9		
TOP MULTI 2		3	178	-	380	-	35		500	500	9.3		
TOP MULTI 3					9.3								
TOP MULTI 4		4			415						10.4		
TOP MULTI 5					10.5								


PALLET CAPACITY

TYPE	GROUPAGE n. pumps	CONTAINER n. pumps
TOP MULTI 1	60	100
TOP MULTI 2	60	80
TOP MULTI 3	60	80
TOP MULTI 4	60	80
TOP MULTI 5	60	80

TOP MULTI 1

MATERIALS AND COMPONENTS

1	Pump body	Technopolymer
2	Suction filter	Technopolymer
3	Containment stages	Technopolymer
4	Impellers	Noryl™
5	Diffusers and stage boxes	Noryl™
6	Diffuser vanes	Technopolymer
7	Motor sleeve	Stainless steel AISI 304
8	Motor cover	Stainless steel AISI 304
9	Motor shaft	Stainless steel AISI 431
10	Mechanical seal	STA-12R Ceramic/Graphite/NBR
11	Shaft seal	Ø 12 x Ø 19 x H 5 mm
12	Capacitor	
13	Electric motor	
14	Handle group Including: - Float switch - Power cable with Schuko plug	
15	Ferrule and hose nozzle	
	Sleeve With built-in clapet valve	



TOP MULTI 2-3-4-5

MATERIALS AND COMPONENTS

1	Delivery port	Technopolymer
2	Pump body	Technopolymer
3	Suction filter	Technopolymer
4	Diffuser vanes	Technopolymer
5	Motor sleeve	Stainless steel AISI 304
6	Impellers	Noryl™
7	Diffusers and stage boxes	Noryl™
8	Motor shaft	Stainless steel AISI 431
9	Double mechanical seal STA-13R Motor side Ceramic/Graphite/NBR STA-13R SIC Pump side SIC/Graphite/NBR	
10	Capacitor	
11	Electric motor	
12	Power cable with Schuko plug	
13	Float switch	
14	Ferrule and hose nozzle	
	Sleeve With built-in clapet valve	
15	Anti-vibration feet	

