

 Clear waters

 Domestic use

※ TOP

**Drainage pumps:
reliable and durable**



PERFORMANCE RANGE

- Flow rate up to **360 l/min** (21.6 m³/h)
- Head up to **15.5 m**

INSTALLATION AND USE

The **TOP** series is excellent for draining **clear water** without abrasive particles. Construction features ensure user-friendly and safe operation, including motor cooling and a double shaft seal. Recommended for emergency drainage of small, flooded areas (rooms, basements, garages), disposing of household water (dishwashers, washing machines), and emptying sumps.

APPLICATION LIMITS

- Liquid temperature up to **+40 °C** and up to **+90 °C** for short bursts (up to 3 minutes max) for intermittent service
- Capable of processing suspended solids up to **Ø 10 mm**
- Draining capability:
 - up to **14 mm** from the bottom for TOP 1-2-3
 - up to **30 mm** from the bottom for TOP 4-5
- Maximum operating depth below water level:
 - up to **3 m** for TOP 1-2-3
 - up to **5 m** for TOP 4-5
 (with an appropriately sized power cable)

PATENTS - TRADE MARKS - MODELS

- Patent No. IT0001428923
- Registered Community Model No. 342159-0011

INCLUDES

- ※ **5 m** power cable
- ※ Float switch

AVAILABLE UPON REQUEST

- ※ Mechanical seal options available
- ※ Different voltage or frequency
- ※ Power cable length **10 m**
- ※ **TOP-GM** " pumps with magnetic float operation (suitable for small sumps)
- ※ **TOP-LA** " special pumps with all metal components in contact with the pumped liquid in AISI 316 stainless steel




※ TOP LA



※ TOP GM

CURVES AND PERFORMANCE DATA

60 Hz



TYPE Single-phase	POWER (P ₂)		Q	m ³ /h	0	1.2	2.4	3.6	4.8	6.0	7.2	8.4	9.6	10.8	12.0	13.2	14.4	15.6	18.0	19.2	21.6
	kW	HP		l/min	0	20	40	60	80	100	120	140	160	180	200	220	240	260	300	320	360
TOP 1	0.25	0.33	H m	6.5	6	5.5	5	4.4	3.7	3	2	1									
TOP 2	0.37	0.50		8.5	8	7.5	7	6.5	6	5.3	4.6	3.8	3	2	1						
TOP 3	0.55	0.75		10.4	10	9.6	9	8.6	8	7.5	7	6.3	5.5	4.8	4	3	2				
TOP 4	0.75	1		13	12.5	12	11.6	11	10.6	10	9.5	8.8	8.2	7.4	6.7	6	5	3	2		
TOP 5	0.92	1.25		15.5	15	14.5	14	13.6	13	12.6	12	11.4	10.8	10	9.4	8.7	7.8	6	5	2.5	

Q = Flow rate H = Total manometric head

Performance curves comply with EN ISO 9906 Grade 3B tolerance limits.


ABSORPTION

TYPE Single-phase	VOLTAGE 220 V
TOP 1	1.5 A
TOP 2	2.2 A
TOP 3	3.7 A
TOP 4	5.0 A
TOP 5	6.0 A


TYPE Single-phase	VOLTAGE 110 V
TOP 1	3.0 A
TOP 2	4.5 A
TOP 3	8.6 A
TOP 4	9.8 A
TOP 5	—

✘ TOP-LA and TOP-GM pumps have the same performance

DIMENSIONS AND WEIGHT




Typical installation




TYPE	PORT	DIMENSIONS mm							kg
Single-phase	DN	a	h	h1	d	e	p	Ø	
TOP 1	1¼"	152	260	240	14	adjustable	350	350	5.4
TOP 2			290	270					5.4
TOP 3									6.7
TOP 4	1½"	204	337	313	30		450	450	10.3
TOP 5									11.3

※ TOP-LA pumps have the same dimensions

※ Version with 'GM' magnetic float switch



Typical installation



TYPE	PORT	DIMENSIONS mm									kg
Single-phase	DN	a	b	h	h1	d	e	g (adjustable)	p	Ø	
TOP 1 - GM	1¼"	152	200	260	240	14	140	35	350	220	5.4
TOP 2 - GM											5.4
TOP 3 - GM											6.9
TOP 4 - GM	1½"	204	-	337	313	30	220	65	450	300	10.5
TOP 5 - GM											11.4

PALLET CAPACITY

TYPE	GROUPAGE	CONTAINER
Single-phase	n. pumps	n. pumps
TOP 1	96	144
TOP 2	96	144
TOP 3	96	144
TOP 4	60	100
TOP 5	60	100


TYPE	GROUPAGE	CONTAINER
Single-phase	n. pumps	n. pumps
TOP 1 - GM	80	120
TOP 2 - GM	80	120
TOP 3 - GM	80	120
TOP 4 - GM	45	60
TOP 5 - GM	45	60

TOP 1-2-3

MATERIALS AND COMPONENTS

1	Pump body	Technopolymer		
2	Suction filter	Technopolymer		
3	Suction cover	Stainless steel AISI 304 (for TOP-LA versions AISI 316L)		
4	Diffuser	Technopolymer		
5	Impeller	Noryl™		
6	Motor sleeve	Stainless steel AISI 304 (for TOP-LA versions AISI 316L)		
7	Motor cover	AISI 304 stainless steel		
8	Motor shaft	Stainless steel AISI 431 (for TOP-LA versions AISI 316L)		
9	Mechanical seal			
	Water pump	Seal	Shaft	Materials
	TOP 1-2-3	STA-12R	Ø 12 mm	Ceramic / Graphite / NBR
	TOP 2-3 LA	AR-12R LA	Ø 12 mm	Ceramic / Graphite / NBR
10	Sealing ring Ø 12 x Ø 19 x H 5 mm			
11	Capacitor			
12	Electric motor TOP: single-phase 220 V - 60 Hz or 110 V - 60 Hz with winding integrated thermal motor protection - Continuous duty S1 - Insulation: class F - Protection rating IP X8			
13	Handle group Complete with – 5 m power cable type 'H07 RN-F' with Schuko plug – Float switch (vertical operation in GM versions)			
14	Ferrule and hose nozzle			
	Hose connector Ø 25 mm for TOP 1 Ø 35 mm for TOP 2-3			





TOP 4-5

MATERIALS AND COMPONENTS

1	Pump body	Technopolymer		
2	Suction filter	Technopolymer		
3	Suction cover	Stainless steel AISI 304		
4	Diffuser	Technopolymer		
5	Impeller	Noryl™		
6	Motor sleeve	Stainless steel AISI 304		
7	Motor cover	Stainless steel AISI 304		
8	Motor shaft	Stainless steel AISI 431		
9	Double mechanical seal with interposed oil chamber			
	Seal	Shaft	Location	Materials
	MG1-14D SIC	Ø 14 mm	Motor side	SiC / Graphite / NBR
			Pump side	SiC / SiC / NBR
10	Capacitor			
11	Electric motor			
	TOP: single-phase 220 V - 60 Hz or 110 V - 60 Hz with winding integrated thermal motor protection			
	- Continuous duty S1 - Insulation: class F			
	- Protection rating IP X8			
12	Handle group			
	Including:			
	– 5 m power cable type 'H07 RN-F' with Schuko plug			
	– Float switch (vertical operation in GM versions)			
13	Sleeve	Threaded technopolymer 1½" with clapet valve		
				
14	Ferrule and hose nozzle	Hose connector Ø 41 mm		
				

