



# SIHI® Z-LINE

## Modular Industrial Pumps



*Experience In Motion*



## SIHI® Z-Line— Robust, Reliable, Efficient ...

Broad application suitability underpins the SIHI Z-line range of end-suction centrifugal pumps. Demanding temperature profile, hydraulic efficiency, low NPSH make this range a perfect choice for those making an ecologically balanced decision. Designed according to EN733 and ISO9908, assures long-term reliability, process consistency, and simple maintenance.

Three configurations of the SIHI Z-Line range combine modularity with application fit. The general purpose end- suction design is complemented by two additional models for hot water and hot oil. All three designs are fundamentally different in which to match the different demands of each application.

Developed in accordance with some strict ISO, DIN, and EN standards guarantees the quality and market interchangeability of the SIHI Z-Line. Highly effective seal chamber design is at the heart of this range, where seal face lubrication is of paramount importance for reliability. Overhung single-stage impeller permits only one set of bearings, one seal configuration, and back pull-out together with the other benefits of end-suction.

Over 38 hydraulic sizes are available long or close-coupled, horizontal or vertical in-line, in various materials, and with multiple sealing options.

- Water supply
- Irrigation
- Food and beverage
- Potable water
- Light Chemical
- Pharmaceutical

- Metal manufacture
- Rubber & Plastic
- Marine
- Paper & Pulp
- Tank Farm Storage
- Building and construction services
- Textile

### Performance Range

- Capacity: max. 740 m<sup>3</sup>/h (3258 Us gpm)<sup>1)</sup>
- Head: max. 140 m (459 ft)<sup>2)</sup>
- Speed: max. 3600 rpm
- Casing pressures: max. 40 bar (580 psi)
- Temperatures: max. + 350 °C (662 °F)<sup>3)</sup>

- 1) For higher capacities up to 2200 m<sup>3</sup>/h (9687 Us gpm) we recommend the CBT range
- 2) For higher heads up to 1600 m (5249 ft) we recommend the Multi range
- 3) For higher temperatures up to 400 °C (752 °F) we recommend the ISOchem range

### Materials

- Cast iron
- Ductile iron
- Stainless steel


### Sealing options

- Mechanical seal
- Gland packing



## General Purpose Pumps

**Horizontal End Suction Volute Casing Pumps** *according to EN 733*



**ZLN** long-coupled design with single or double mechanical seal, or packed gland. Optional possibilities include seal quench, cooling, heating, flushing, and throttling.

**ZLK** close-coupled design with single mechanical seal.

**In-Line Volute Casing Pumps** *according to EN 733*



**ZLI** close-coupled design with single mechanical seal.

General Purpose Pumps	Capacity (maximum)	Head (maximum)	Speed (maximum)	Temperature (maximum)	Casing Pressure	Sealing	Materials
ZLN	740 m <sup>3</sup> /h (3258 US gpm)	140 m (459 ft)	3600 rpm	170 °C (338 °F)	16 bar (232 psi)	Mechanical seal, gland packing	Cast iron, Ductile Iron stainless steel
ZLK	740 m <sup>3</sup> /h (3258 US gpm)	90 m (295 ft)	3600 rpm	120 °C (248 °F)	16 bar (232 psi)	Mechanical seal	Cast iron, stainless steel
ZLI	330 m <sup>3</sup> /h (1453 US gpm)	60 m (197 ft)	3600 rpm	120 °C (248 °F)	16 bar (232 psi)	Mechanical seal	Cast iron, stainless steel

## ZLN Design Features

Suitable for temperatures up to 170 °C (338 °F), this diverse range of general purpose pumps offers the user a low life-cycle cost solution. Capital cost, power consumption, maintenance, reliability, and waste, have all been considered during the extensive development phase.

### Long lasting efficiency

- Closed impeller permitting 'neck' wear-rings to be retrofitted

### High efficiency & low power

- Advanced fluid dynamic design

### Low NPSH


- High quality impeller and suction profile

### Extended seal life

- Vortex breakers and modern seal chamber
- Low shaft deflection

### Flexible sealing options

- Single or double mechanical seals
- component seals
- Packed gland



### Robust rotating assembly

- Oversized ball bearings and shaft diameter
- Bearing bracket rigidly fixed to the casing cover for stable back pull-out transportation

### Reliability

- Seal area shaft deflection to ISO 5199
- Totally agree with EN733 / DIN24255 and ISO9908


### Mechanical seal protection

- Improved security thanks to use a polypropylene seal guard



## Hot Water Pumps up to 230°C (446°F)

**Horizontal End Suction Volute Casing Pumps** according to EN 733 or EN 22858



**ZHN** long-coupled. Designed specifically for use with pressurized high-temperature water without the need to cool the single mechanical seal. Main dimensions in accordance with EN 733.

**ZDN** long-coupled. Designed specifically for use with pressurized high-temperature water without the need to cool the single mechanical seal. Main dimensions in accordance with EN 22858.

**ZEN** long-coupled. Designed specifically for use with pressurized high-temperature water without the need to cool the single mechanical seal. Main dimensions in accordance with EN 22858.

**In-Line Volute Casing Pumps** according to EN 733



**ZDI** close-coupled design with single mechanical seal that does not need to be cooled.

Hot Water Pumps	Capacity (maximum)	Head (maximum)	Speed (maximum)	Temperature (maximum)	Casing Pressure	Sealing	Materials
ZHN	600 m <sup>3</sup> /h (2642 US gpm)	95 m (311 ft)	3600 rpm	180 °C (356 °F) un-cooled	16 bar (232 psi)	Mechanical seal	Ductile iron
ZDN	600 m <sup>3</sup> /h (2642 US gpm)	90 m (295 ft)	3600 rpm	207 °C (404 °F) un-cooled	25 bar (362 psi)	Mechanical seal	Ductile iron
ZEN	600 m <sup>3</sup> /h (2642 US gpm)	90 m (295 ft)	3600 rpm	230 °C (446 °F) un-cooled	40 bar (580 psi)	Mechanical seal	Ductile iron
ZDI	140 m <sup>3</sup> /h (616 US gpm)	60 m (196 ft)	3600 rpm	150 °C (302 °F) un-cooled	25 bar (362 psi)	Mechanical seal	Ductile iron

## ZHN Design Features

Superior hot water circulation, up to 230°C (446 °F) with a standard un-cooled mechanical seal, gives the unique ability to minimize life-cycle cost. Internal separation and removal of undesirable vapour (steam) enhances mechanical seal face lubrication and improves reliability. High-level hydraulic efficiency ensures that running costs are predictably low.

### Long lasting efficiency

- Closed impeller permitting 'neck' wear-rings to be retrofitted

### High efficiency

#### & low power

- Advanced fluid dynamic design

### Low NPSH

- High quality impeller and suction profile

### Robust rotating assembly

- Long-life ball bearing
- Sleeve bearing

### Simple removal

- Back pull-out design

### Un-cooled seal


- Vapour separation and removal in this unique seal chamber
- Large volume seal chamber located at cool drive-end
- Low shaft deflection

### Long life

- Anti-friction bearing

### Reduced spare parts cost

- Standard mechanical seal to DIN 24960



### Stable with temperature fluctuations

- Provision for thermal expansion



## Thermal oil Pumps up to 350°C (662°F)

Horizontal End Suction Volute Casing Pumps according to EN 733



350°C  
662 °F



**ZTN** long-coupled. With auxiliary seal security, these units are designed specifically for use with high-temperature thermal oils. Main dimensions in accordance with EN 733.

**ZTK** close-coupled. The addition of a shaft mounted air-cooling fan, together with the auxiliary seal security, makes the ZTK a perfect solution for high-temperature thermal oils. Main dimensions in accordance with EN 733.

## In-Line Volute Casing Pumps according to EN 733



350°C  
662 °F



**ZTI** close-coupled in-line. The addition of a shaft-mounted air-cooling fan, together with the auxiliary sealing options, makes the ZTI an ideal selection for high-temperature thermal oils where space is at a premium.

Thermal Oil Pumps	Capacity (maximum)	Head (maximum)	Speed (maximum)	Temperature (maximum)	Casing (maximum)	Sealing Pressure	Materials
ZTN	740 m <sup>3</sup> /h (3258 US gpm)	90 m (295 ft)	3600 rpm	350 °C (662 °F) un-cooled	16 bar (232 psi)	Mechanical seal, Seal ring	Ductile iron
ZTK	200 m <sup>3</sup> /h (880 US gpm)	60 m (196 ft)	3600 rpm	350 °C (662 °F) un-cooled	16 bar (232 psi)	Mechanical seal	Ductile iron
ZTI	200 m <sup>3</sup> /h (880 US gpm)	60 m (196 ft)	3600 rpm	350 °C (662 °F) un-cooled	16 bar (232 psi)	Mechanical seal	Ductile iron

## ZTN Design Features

Operational safety, environmental concern, and long-term reliability, are the three aspects which make this pump an ideal choice for thermal oils up to 350 °C (662 °F). High-end hydraulic efficiency is complimented by almost maintenance-free operation, in which to give a low Life-Cycle cost solution. Shaft sealing is a combination of mechanical and secondary lip seals,

### Long lasting efficiency

- Closed impeller permitting 'neck' wear-rings to be retrofitted

### High efficiency & low power

- Advanced fluid dynamic design

### Low NPSH

- High quality impeller and suction profile

### Robust rotating assembly

- Long-life ball bearing
- Sleeve bearing

### Stable with temperature fluctuations


- Provision for thermal expansion

### Simple removal

- Back pull-out design

### Triple protection

- Mechanical seal backed by lip seals and bearing assembly





### Reduced spare parts cost

- Standard mechanical seal to DIN 24960 and basic lip seals
- \* No external cooling

### Enhanced seal life

- Heat dissipation with air-fin cooling





## Features


- High efficiency
- Seal area deflection to ISO 5199
- Low NPSH
- Modular family
- Back pull-out
- Global service network
- ATEX

## Benefits

- Reduced power consumption
- High reliability & extended MTBF
- Reduced installation costs
- Low inventories, short delivery times
- Ease of maintenance
- Local and rapid support
- Suitable for explosive atmospheres

<b>Horizontal End Suction Volute Casing Pumps</b> <i>according to EN 733</i> 	<b>General Purpose Pumps</b>  <i>ZLN long-coupled design up to 170°C (338 °F)</i>	 <i>ZLK close-coupled design up to 120°C (248 °F)</i>
<b>Hot Water Pumps</b>		
 <i>ZHN long-coupled design up to 180°C (356 °F)</i>	 <i>ZDN long-coupled design up to 207°C (404.6 °F)</i>	 <i>ZEN long-coupled design up to 230°C (446 °F)</i>

### Thermal Oil Pumps



ZTN long-coupled design up to 350°C (662 °F)



ZTK close-coupled design up to 350°C (662 °F)

### In-Line Volute Casing Pumps

based on EN 733



### General Purpose Pumps



ZLI close-coupled design up to 120°C (248 °F)

### Hot Water Pumps



ZDI close-coupled design up to 150°C (302 °F)

### Thermal Oil Pumps



ZTI close-coupled design up to 350°C (662 °F)





---

Flowserve Corporation  
5215 North O'Connor Blvd.  
Suite 700  
Irving, Texas 75039-5421 USA

**PUBR003146-00 (EN/A4)** July 2025

Flowserve Corporation has established industry leadership in the design and manufacture of its products. When properly selected, this Flowserve product is designed to perform its intended function safely during its useful life. However, the purchaser or user of Flowserve products should be aware that Flowserve products might be used in numerous applications under a wide variety of industrial service conditions. Although Flowserve can provide general guidelines, it cannot provide specific data and warnings for all possible applications. The purchaser/user must therefore assume the ultimate responsibility for the proper sizing and selection, installation, operation, and maintenance of Flowserve products. The purchaser/user should read and understand the Installation Instructions included with the product, and train its employees and contractors in the safe use of Flowserve products in connection with the specific application.

While the information and specifications contained in this literature are believed to be accurate, they are supplied for informative purposes only and should not be considered certified or as a guarantee of satisfactory results by reliance thereon. Nothing contained herein is to be construed as a warranty or guarantee, express or implied, regarding any matter with respect to this product. Because Flowserve is continually improving and upgrading its product design, the specifications, dimensions and information contained herein are subject to change without notice. Should any question arise concerning these provisions, the purchaser/user should contact Flowserve Corporation at any one of its worldwide operations or offices.

©2025 Flowserve Corporation. All rights reserved. This document contains registered and unregistered trademarks of Flowserve Corporation. Other company, product, or service names may be trademarks or service marks of their respective companies.